

LEDDRL301

LEDDriving PX-5 | – LED daytime running lights



Areas of application

- Daytime running light

Product benefits

- 3 year guarantee
- Low energy consumption
- Easy installation
- Suitable for many vehicle models
- Modern dotted diode effect
- Automatic dimming mode at night
- Dynamic appearance thanks to faceted optic and dotted LED technology
- Mountable into narrow bumper grids thanks to slim design and specific shape

Product features

- LED daytime running light
- Color temperature: up to 5,200 K
- Number of LEDs: 5
- Long lifetime: up to 5,000 h
- Certified according to ECE, SAE, CCC regulations
- Type of protection: IP67K

Product datasheet

Technical data

Electrical data

Nominal voltage	13.2 V
Nominal wattage	12.5 W

Dimensions & weight

Length	160.0 mm
Product weight	552.00 g

Country specific categorizations

Order reference	LEDDRL301 BK 12
-----------------	-----------------

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321781215	LEDDRL301	Folding carton box 1	327 mm x 53 mm x 243 mm	4.21 dm ³	790.00 g
4008321781222	LEDDRL301	Shipping carton box 4	348 mm x 268 mm x 265 mm	24.71 dm ³	3614.00 g
4052899089563	LEDDRL301	Shipping carton box 5	444 mm x 305 mm x 231 mm	31.28 dm ³	4870.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

Guarantee terms are available at

▶ www.osram.com/am-guarantee

Legal advice

ECE E4 approval

ECE R87 approval

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.