







Overview

T-CHARGE 12 6V/12V

cod. 807567

Multifunction, battery charger and maintainer for 6/12V WET, GEL, AGM, MF, PbCa, EFB batteries.

Choice of 3 charge voltages in Pulse Tronic: 6V, 12V/1A (motos), 12V/4A (autos).


Advanced specific functions for the charge and maintenance of batteries at low temperatures and of AGM batteries.

The activation of the RECOVERY function allows for the recovery of sulphated batteries.

Features:

- Automatic charge and maintenance in Pulse Tronic;
- 3 charge voltages;
- Led visualization of the charge level;
- AGM function for the charge and maintenance of AGM batteries;
- COLD function to charge and maintain batteries at low temperatures;
- RECOVERY function to recover sulphated batteries;
- Protections against overloads, shortcircuit and polarity reversal.

Equipped with cable with clamps and cable with eyelets.



Technical data





T-CHARGE 12 6V/12V



CODE 807567



EFFECTIVE CHARGING CURRENT 1 / 4 A



DIMENSIONS 17 - 6,5 - 3,5 cm



SINGLE PHASE MAINS VOLTAGE 230 V



RATED CHARGE CURR. EN60335-2-29



WEIGHT 0,6 kg



MAINS FREQUENCY 50 - 60 Hz



MIN. RATED REFERENCE CAPACITY 2



EAN CODE 800489798045 4



CHARGING ABSORBED POWER 55 W



MAX RATED REFERENCE CAPACITY 70



PIECES/PALLET 432 pz/pallet



CHARGING VOLTAGE 6 / 12 V



ADJUSTMENT POSITIONS 2



PIECES/PALLET - B 288 pz/pallet - B